

Engen Gearlube Multi 75W-90

Automotive Gear Lubricant

Description

This automotive gear lubricant contains sulphur-phosphorus EP (Extreme Pressure) additives and is specially recommended for synchromesh transmissions where it provides full protection to bronze components, ensure reliable operation and smooth gear changes. It meets API Service Classification GL-4.

Application

Engen Gearlube Multi 75W-90 is suitable for transmission/axle combinations, synchromesh gearboxes and other applications which require a relatively low level of EP additives. Engen Gearlube Multi 75W-90 oil is also recommended for manual transmissions.

Performance Level

API GL-4 and MIL-L-2105

Benefits

- Protects against wear
- Smooth gear changing
- Prevents corrosion
- Excellent high and low temperature performance

Typical Physical Characteristics

Engen Gearlube Multi 75W-90	
SAE No.	75W-90
Viscosity, cSt @ 40 °C	105
Viscosity, cSt @ 100 °C	13,8
Viscosity Index	170
Flash Point, °C	212
Pour Point, °C	-42

02.2015

Due to continual product research and development, the information contained herein is subject to change without notification. Refer to the Material Safety Data Sheet (MSDS) for information on the safe handling and use of this product.

Engen Petroleum Ltd | Tel: 08600 36436 | Website: www.engenoil.com | Email: 1call@engenoil.com